

WHAT IS CLAIMED IS:

1 1. In a computer system including at least two
2 server nodes, each of which execute clustered server
3 software, a method for providing a transition from a
4 first one of said server nodes to a second one of said
5 server nodes, said method comprising the steps of:

6
7 a. in response to a request for said
8 transition, initiating a thread for effecting
9 said transition from said first server node to
10 said second server node;

11
12 b. determining if a shared resource is owned
13 by said second node, and if not;

14
15 c. calling a driver to enable functionality
16 of said transition, which transition sets up
17 said shared resource access to said second
18 server node.

19
1 2. The method as in Claim 1, further including a
2 step of counting the number of resources that have
3 transitioned.

4
1 3. The method as in Claim 1 wherein said
2 transition occurs when said first server has failed and
3 said resource is brought online on said second server.

1
2 4. The method as in Claim 1 wherein said
3 transition occurs when a server becomes active following
4 a failure and said resource is brought online on said
5 first server and offline on said second server.

6

1 5. The method as in Claim 1 wherein said
2 transition occurs in response to a selection by a user.

3

1 6. The method as in Claim 5 wherein said
2 transition occurs in response to said user selection so
3 that said resource is brought online on said second
4 server.

5

1 7. The method as in Claim 5 wherein said
2 transition occurs in response to said user selection so
3 that said resource is brought online on said first server
4 and offline on said second server.

5

1 8. A storage medium encoded with machine-readable
2 computer program code for providing a transition from a
3 first one of said server nodes to a second one of said
4 server nodes, wherein, when the computer program code is
5 executed by a computer, the computer performs the steps
6 of:

7 a. in response to a request for said
8 transition, initiating a thread for effecting
9 said transition from said first server node to
10 said second server node;

11

12 b. determining if a shared resource is owned
13 by said second node, and if not;

14

15 c. calling a driver to enable functionality
16 of said transition, which transition sets up
17 said shared resource access to said second
18 server node.

19

1 9. The storage medium as in Claim 8, further
2 including a step of counting the number of resources that
3 have transitioned.

4

1 10. The storage medium as in Claim 8 wherein said
2 transition occurs when said first server has failed and
3 said resource is brought online on said second server.

1

2 11. The storage medium as in Claim 8 wherein said
3 transition occurs when a server becomes active following
4 a failure and said resource is brought online on said
5 first server and offline on said second server.

6

1 12. The storage medium as in Claim 8 wherein said
2 transition occurs in response to a selection by a user.

3

1 13. The storage medium as in Claim 12 wherein said
2 transition occurs in response to said user selection so
3 that said resource is brought online on said second
4 server.

5

1 14. The storage medium as in Claim 12 wherein said
2 transition occurs in response to said user selection so
3 that said resource is brought online on said first server
4 and offline on said second server.